

Markwik 21 Bib Mixer Thermomostatic, Sensor Proximity, Bioguard

ILLUSTRATED

A6737 (TB H6) Markwik 21+ panel mounted thermostatic basin mixer, time flow sensor, demountable with fixed spout

ILLUSTRATED PRODUCT DETAILS

Weights

A6737 3.60 KG

Finishes

A6737  Chrome (AA)

Materials

A6737 Chrome Plated Brass

Standards

Conforms to HTM64 (2006), HTM04-01, HFN30.

Special Notes

This product is fitted with an Armitage Bioguard outlet which reduces the opportunity for bio film attachment and is lined with anti-microbial copper.

Tap is activated by movement in the proximity of the sensor and stops immediately when both movement and proximity stop.

Hygienic automatic flush can be set to occur every 6, 12, 24, 48 or 72 hours.

Unique built-in thermal disinfection cleansing feature using kit S8239NU a bridging hose which is re-usable. A purging tool A4556AA is also available to facilitate initial installation or aid in system disinfection.

* Line drawing shows recommended height over washbasin. Especially suited to medium and large hospital pattern integral back outlet basins and washing associated with clinical or nursing procedures.

Flow rate regulated to maximum of 10 Litres per minute.



ACCREDITATIONS



FEATURES

