

## Concept 180cm x 80cm Rectangular Idealform Bath

### ILLUSTRATED

|              |                                                                                                 |
|--------------|-------------------------------------------------------------------------------------------------|
| <b>E1639</b> | Concept 180cm x 80cm rectangular Idealform bath with no taphole                                 |
| <b>A7051</b> | Connect Air single lever 2 tap hole bath filler                                                 |
| <b>E4798</b> | Unilux Plus+ 180cm front panel                                                                  |
| <b>S8970</b> | Trap 1½" plastic P with 75mm seal, multi-purpose outlet suitable for plastic and BS copper pipe |
| <b>E1486</b> | Luxury bath pop-up waste and overflow                                                           |
| <b>A5901</b> | TMV thermostatic mixing valve, 22mm                                                             |

### OPTIONS

|              |                             |
|--------------|-----------------------------|
| <b>E4833</b> | Unilux Plus+ 80cm end panel |
|--------------|-----------------------------|

### ILLUSTRATED PRODUCT DETAILS

#### Weights

|              |          |
|--------------|----------|
| <b>E1639</b> | 25.30 KG |
| <b>A7051</b> | 2.83 KG  |
| <b>E4798</b> | 3.50 KG  |
| <b>S8970</b> | 1.00 KG  |
| <b>A5901</b> | 0.60 KG  |

#### Materials

|              |                         |
|--------------|-------------------------|
| <b>E1639</b> | Idealform               |
| <b>A7051</b> | Chrome Plated Brass     |
| <b>E4798</b> | High Impact Polystyrene |
| <b>S8970</b> | Plastic                 |
| <b>E1486</b> | Mixed Material          |
| <b>A5901</b> | Chrome Plated Metal     |

#### Finishes

|              |                                                                                                            |
|--------------|------------------------------------------------------------------------------------------------------------|
| <b>E1639</b> |  White (01)               |
| <b>A7051</b> |  Chrome (AA)              |
| <b>E4798</b> |  White (01)              |
| <b>S8970</b> |  Neutral/No Finish (67) |
| <b>E1486</b> |  Chrome (AA)            |
| <b>A5901</b> |  Chrome (AA)            |

#### Capacity

|              |                            |
|--------------|----------------------------|
| <b>E1639</b> | 260.0 litres (to overflow) |
|--------------|----------------------------|

#### Flow rates

|              |                                       |
|--------------|---------------------------------------|
| <b>A7051</b> | 26 Litres per minute @ 3 bar pressure |
|--------------|---------------------------------------|

#### Designer

Robin Levien, RDI

### FINISH OPTIONS

|                                                                                     |                                                                                     |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |
| (AA) Chrome                                                                         | (A2) Brushed Gold                                                                   | (A5) Magnetic Grey                                                                  |
|  |                                                                                     |                                                                                     |
| (GN) Silver Storm                                                                   |                                                                                     |                                                                                     |

#### Standards

Constructed to EN 198:2008. EN 14516

#### Special Notes

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device see A5901AA or Part G for guidance. One tap hole fittings require offsetting from the overflow. Check positioning and compatibility before specifying.

E: [info@idealspec.co.uk](mailto:info@idealspec.co.uk) | T: 0870 122 8822 | F: 0870 122 8282 | [www.idealspec.co.uk](http://www.idealspec.co.uk)

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.

