

Tempo Cube 170cm x 75cm Idealform Bath No Handgrips No Tapholes

ILLUSTRATED

- E2582** Tempo Cube 170cm x 75cm Idealform bath, no handgrips or tapholes
- B0730** Tempo 2 hole bath filler
- E3194** Unilux 170cm front panel
- E3195** Unilux 75cm end panel
- S8970** Trap 1½" plastic P with 75mm seal, multi-purpose outlet suitable for plastic and BS copper pipe
- E1486** Luxury bath pop-up waste and overflow
- A5901** TMV thermostatic mixing valve, 22mm

OPTIONS

- B0731** Tempo 2 hole bath shower mixer
- B0732** Tempo 1 hole bath filler
- B0733** Tempo 1 hole bath shower mixer
- S8830** Waste 1½" bath chain and overflow, plastic plug

ILLUSTRATED PRODUCT DETAILS








Weights

- E2582** 23.00 KG
- B0730** 2.64 KG
- E3194** 3.65 KG
- E3195** 2.58 KG
- S8970** 1.00 KG
- A5901** 0.60 KG

Materials

- E2582** Idealform
- B0730** Chrome Plated
- E3194** Acrylic
- E3195** Acrylic
- S8970** Plastic
- E1486** Mixed Material
- A5901** Chrome Plated Metal

Finishes

- E2582**  White (01)
- B0730**  Chrome (AA)
- E3194**  White (01)
- E3195**  White (01)
- S8970**  Neutral / No Finish (67)
- E1486**  Chrome (AA)
- A5901**  Chrome (AA)

Capacity

- E2582** 200.0 litres (to overflow)

Flow rates

- B0730** 50 Litres per minute @ 3 bar pressure

Designer

Robin Levien, RDI

Standards

Constructed to EN 198:2008. EN 14516

Special Notes

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device, see A5901AA or Part G for guidance. One taphole fittings require offsetting from the overflow. Check positioning and compatibility before specifying.

