Concept 150cm x 70cm Bath 2 Tapholes

ILLUSTRATED

| E7297 | Concept 150cm x 70cm bath with 2 tapholes |
|-------|---|
| E4180 | Uniline 150cm front bath panel |
| E4140 | Uniline 70cm end panel |
| E1486 | Luxury bath pop-up waste and overflow |
| A5901 | TMV thermostatic mixing valve, 22mm |
| | |

OPTIONS

| BD264 | Ceraplan dual control bath filler |
|-------|---|
| S8970 | Trap 1½" plastic P with 75mm seal, multi-purpose outlet |
| | suitable for plastic and BS copper pipe |

ILLUSTRATED PRODUCT DETAILS

| Weights | | Finishes | | |
|-----------|-------------------------|----------|-----|-------------|
| E7297 | 19.40 KG | E7297 | | White (01) |
| E4180 | 3.30 KG | | | |
| E4140 | 1.80 KG | E4180 | | White (01) |
| A5901 | 0.60 KG | | | |
| Materials | | E4140 | | White (01) |
| E7297 | Idealform | | | |
| E4180 | High Impact Polystyrene | E1486 | - A | Chrome (AA) |
| E4140 | High Impact Polystyrene | | | |
| E1486 | Mixed Material | A5901 | | Chrome (AA) |
| A5901 | Chrome Plated Metal | | | |
| | | Capacity | | |

E7297 149.0 litres (to overflow)

Designer

Robin Levien, RDI


Standards


Constructed to EN 198:2008. EN 14516

Special Notes

Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device, see A5901AA or Part G for guidance. One taphole fittings require offsetting from the overflow. Check positioning and compatibility before specifying.







ACCREDITATIONS



FEATURES



