

# Contour 21 Wall Mounted WC Pan 75cm Proj - Doc M Sensorflow Individual Items

## ILLUSTRATED

- S0442** Contour 21+ 75cm projection wall mounted rimless WC pan with horizontal outlet and anti-microbial glaze
- S2474** Contour 21 37cm handrinse washbasin right hand taphole no overflow or chainstay hole, bottom outlet
- S9110** Hangers concealed, Steel
- S8900** Trap 1¼" metal bottle, 75mm seal, outlet screwed 1¼" BSP male with compression nut and ring
- A4852** Sensorflow 21 compact washbasin mounted spout with integral sensor, 3.7 litre per minute aerated spray outlet, combined inlet servicing valve and filter, mains
- S6362** Contemporary 21 hinged support rail, 80cm Doc M Compliant
- A5900** TMV thermostatic mixing valve, 15mm
- N1381** Concept toilet roll holder
- S0830** Contemporary 21 60cm contemporary grab rail
- S0831** Contemporary 21 45cm contemporary grab rail
- S8810** Waste 1¼" plastic strainer, dished pattern 80mm unslotted tail
- S3334** Conceala 3 Sensorflow 21 single flush 6 litre cistern, easy adjustable to low water volumes (4.5 or 4 litres), bottom/top inlet, panel mounted touch free sensor actuation, internal overflow, flushpipe included
- S4066** Contour 21 toilet seat only, top fixing hinges and retaining buffers
- S9139** Support bracket for wall mounted WC raised height with bolts
- S6637** Multi-System back support, white, complete with cushion










## FEATURES



## OPTIONS

- S4303** Contour 21 outlet extension connector for 70/75cm WC pan outlet

## ILLUSTRATED PRODUCT DETAILS

Sizes		Finishes	
<b>S2474</b>	w:370 x d:300	<b>S0442</b>	 White With SmartGuard (HY)
<b>Weights</b>		<b>S2474</b>	 White (01)
<b>S0442</b>	37.00 KG	<b>S9110</b>	 Neutral/No Finish (67)
<b>S2474</b>	7.50 KG	<b>S8900</b>	 Chrome (AA)
<b>S9110</b>	0.24 KG	<b>A4852</b>	 Chrome (AA)
<b>S8900</b>	0.54 KG	<b>S6362</b>	 Chrome finish (AA)
<b>A4852</b>	1.60 KG	<b>A5900</b>	 Chrome (AA)
<b>S6362</b>	3.00 KG		
<b>A5900</b>	0.50 KG		
<b>N1381</b>	0.78 KG		
<b>S0830</b>	4.26 KG		
<b>S0831</b>	3.20 KG		
<b>S8810</b>	0.04 KG		
<b>S3334</b>	3.15 KG		
<b>S4066</b>	1.55 KG		
<b>S9139</b>	4.28 KG		

E: [info@idealspec.co.uk](mailto:info@idealspec.co.uk) | T: 0870 122 8822 | F: 0870 122 8282 | [www.idealspec.co.uk](http://www.idealspec.co.uk)

Ideal Standard (UK) Ltd. makes every effort to ensure that the information provided on its website is accurate. However, we cannot guarantee this, and accept no liability for any information or advice given via its website.



# Contour 21 Wall Mounted WC Pan 75cm Proj - Doc M Sensorflow Individual Items

**S6637** 3.63 KG

**Materials**


- S0442** Vitreous China
- S2474** Vitreous China
- S9110** Metal
- S8900** Chrome Plated Brass
- A4852** Chrome Plated Brass
- S6362** Aluminium
- A5900** Chrome Plated Metal
- N1381** Chrome Plated Metal
- S0830** Aluminium
- S0831** Aluminium
- S8810** Plastic
- S3334** Plastic
- S4066** Plastic
- S9139** Metal
- S6637** Mixed Material

**N1381**  Chrome (AA)


**S0830**  Chrome (AA)

**S0831**  Chrome (AA)

**S8810**  White (01)

**S3334**  Neutral/No Finish (67)

**S4066**  White (01)

**S9139**  Neutral/No Finish (67)

**S6637**  White (AC)

**Capacity**

**S2474** 4.5 litres

**S3334** 6.0 litres












**Flow rates**

**A4852** 3.7 Litres per minute @ 3 bar pressure

**Designer**

Robin Levien, RDI

## FINISH OPTIONS

		
(AA) Chrome	(GN) Ultra Steel	(AA) Chrome finish
		
(MY) Stainless Steel	(XG) Silk Black	(01) White
		
(36) Blue	(LJ) Grey	(RN) Charcoal
		
(GQ) Red	(V3) Silk Black	

**Standards**

**Special Notes**

For LRV and RAL numbers see Doc M introduction. For right hand corner arrangement substitute S247401 for S247301.  
 600mm grab rail S6484 x 4 for room set  
 450mm grab rail S6486 is for back of door.  
 Mains powered Sensorflow products must be connected to a continuous permanent power supply of these require 220-240 volts and each 1 having its own fuse spur.  
 When using Conceala 3 pneumatic cisterns, the EW22267 reducer pack is needed for connecting to the constructed flushbend.