Sandringham 21 Steel bath 160cm x 70cm 2 Tapholes With Handgrips & Anti-slip*

ILLUSTRATED

S1834	Sandringham 21 160cm x 70cm standard gauge steel bath with chrome plated grips, two tapholes and anti-slip*
B3309	Sandringham SL 21 2 hole bath filler
S0915	Bath flat front panel
S0916	Bath flat end panel
S9365	Bath panel plastic corner edge strip
S8970	Trap 1 ¹ ⁄ ₂ " plastic P with 75mm seal, multi-purpose outlet suitable for plastic and BS copper pipe
S8840	1 1/2" combination bath waste & trap with overflow and domed clicker
A5901	TMV thermostatic mixing valve, 22mm

ILLUSTRATED PRODUCT DETAILS

Weights		Finishes		
S1834	25.05 KG	S1834		White (01)
B3309	1.68 KG			
S0915	2.14 KG	B3309		Chrome (AA)
S0916	3.50 KG			()
S9365	0.01 KG	S0915		White (01)
S8970	1.00 KG	00010		
S8840	0.31 KG	S0916		White (01)
A5901	0.60 KG	30910		winte (01)
Materials		C02CF		λh h h h h h h h h h
S1834	Porcelain Fnamelled	S9365		White (01)
31034	Steel			
B3309	Chrome Plated Brass	S8970		Neutral / No Finish
S0915	High Impact Polystyrene			(67)
S0916	High Impact Polystyrene	S8840		Chrome (AA)
S9365	Plastic			
S8970	Plastic	A5901		Chrome (AA)
S8840	Plastic			
A5901	Chrome Plated Metal	Connecitu		
-		Capacity		
		S1834	150.0	0 litres (to overflow)

Flow rates

B3309 70 Litres per minute @ 3 bar pressure


Standards

BS 1390:1990. EN 14516

Special Notes


*Anti slip is a resistant finish that reduces the chances of slipping, it does not prevent all slipping. Not suitable in areas involving the use of special chemicals. Framework is required at installation to support rim and secure panel. Panels require trimming to size at installation. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device, see A5901AA or Part G for guidance.







ACCREDITATIONS



FEATURES



E: info@idealspec.co.uk | T: 0870 122 8822 | F: 0870 122 8282 | www.idealspec.co.uk

