

## Sandringham 21 Steel bath 170cmx70cm No Tapholes With Handgrips & Anti-slip\*

### ILLUSTRATED

<b>S1838</b>	Sandringham 21 170cm x 70cm standard gauge steel bath with chrome plated grips, no tapholes and anti-slip*
<b>S9365</b>	Bath panel plastic corner edge strip
<b>S8970</b>	Trap 1½" plastic P with 75mm seal, multi-purpose outlet suitable for plastic and BS copper pipe
<b>S8840</b>	1 1/2" combination bath waste & trap with overflow and domed clicker
<b>A5901</b>	TMV thermostatic mixing valve, 22mm

### OPTIONS

<b>B3309</b>	Sandringham SL 21 2 hole bath filler
<b>S0915</b>	Bath flat front panel
<b>S0916</b>	Bath flat end panel
<b>S8830</b>	Waste 1½" bath chain and overflow, plastic plug

### ILLUSTRATED PRODUCT DETAILS






#### Weights

<b>S1838</b>	27.01 KG
<b>S9365</b>	0.01 KG
<b>S8970</b>	1.00 KG
<b>S8840</b>	0.31 KG
<b>A5901</b>	0.60 KG

#### Materials

<b>S1838</b>	Porcelain Enamelled Steel
<b>S9365</b>	Plastic
<b>S8970</b>	Plastic
<b>S8840</b>	Plastic
<b>A5901</b>	Chrome Plated Metal

#### Finishes

<b>S1838</b>	 White (01)
<b>S9365</b>	 White (01)
<b>S8970</b>	 Neutral / No Finish (67)
<b>S8840</b>	 Chrome (AA)
<b>A5901</b>	 Chrome (AA)

#### Capacity

<b>S1838</b>	160.0 litres (to overflow)
--------------	----------------------------

#### Standards

BS 1390:1990. EN 14516

#### Special Notes

\*Anti-slip is a resistant finish that reduces the chances of slipping, it does not prevent all slipping. Not suitable in areas involving the use of special chemicals. Framework is required at installation to support rim and secure panel. Panels require trimming to size at installation. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device, see A5901AA or Part G for guidance.

