# Nisa Steel Bath 170cm 2 Taphole, No Handgrips

#### **ILLUSTRATED** S1865 Nisa 170cm x 70cm steel bath with 2 tapholes S0915 Bath flat front panel S0916 Bath flat end panel S9365 Bath panel plastic corner edge strip **S8970** Trap 1½" plastic P with 75mm seal, multi-purpose outlet suitable for plastic and BS copper pipe S8830 Waste 1½" bath chain and overflow, plastic plug A5901 TMV thermostatic mixing valve, 22mm

### **OPTIONS**

B9882	Sandringham 21 bath pillar taps, lever handles
B3309	Sandringham St. 21.2 hole bath filler

### **ILLUSTRATED PRODUCT DETAILS**

Weights	<b>;</b>	Finishes	
S1865	47.85 KG	<b>\$1865</b> White (01)	
S0915	2.14 KG		
S0916	3.50 KG	<b>S0915</b> White (01)	
S9365	0.01 KG		
S8970	1.00 KG	<b>S0916</b> White (01)	
S8830	1.78 KG	111e (62)	
A5901	0.60 KG	S9365 White (01)	
Materia	ls	39303 Willie (01)	
S1865	Porcelain Enamelled	S8970 Neutral / No Finish	
	Steel	(67)	
S0915	High Impact Polystyrene	\$8830 Chrome (AA)	
S0916	High Impact Polystyrene	chrome (AA)	
S9365	Plastic	<b>A5901</b> Chrome (AA)	
S8970	Plastic	<b>A5901</b> Chrome (AA)	
S8830	Mixed Material		
A5901	Chrome Plated Metal	Capacity	
		<b>\$1865</b> 169.0 litres (to overflow)	


#### **Standards**

BS 1390:1990. EN 14516


#### **Special Notes**

\*Anti-slip is a resistant finish that reduces the chances of slipping, it does not prevent all slipping. Not suitable in areas involving the use of special chemicals. Framework is required at installation to support rim and secure panel. Panels require trimming to size at installation. Consideration should be given to safe hot water delivery and the use of an appropriate temperature reduction device, see A5901AA or Part G for guidance.





#### **ACCREDITATIONS**



## **FEATURES**



